
bivaq







Material Extruded aluminum **Finish** Polyester powder coating

TECHNICAL DATA

TEJA LOUNGE SOFA Design: Studio La Mamba

106x95x91 41,4"x37,4"x35,8"

Av. J.V. Foix 72-74 08034 Barcelona Spain

Tel.: +34 93 205 75 95 info@bivaq.com www.bivaq.com

BASE

FRAME

1. Material / Finish

Extruded aluminum / Polyester powder coating

2. Material / Finish

Iroko wood / Waterproof sealant

ROPE

Cover material Polyester Core material Polypropylene **UVA** resistance 7 (clasif. max. 8) **Color fastness** 5 (clasif. máx. 5)

CUSHIONS

Material Polyurethane foam 100% polieter fiber Composition

Density 25 Kg/m3

CUSHIONS FABRIC

Material

Vinytex fabric: synthetic fabric made of plastic coated polyester

or Acrylic fabric: 100% solution dyed acrylic.

UVA resistance 7-8 (clasif. max. 8) **Color fastness** 5 (clasif. máx. 5)

COLORS

See available colors at Bivag current Catalog.

MANTEINANCE

Painted aluminum

Clean the surface regularly with warm water and neutr Iroko wood

Use a non-abrasive sponge or cloth.

Rinse with plenty of water immediately after cleaning.

Rope & cushions

It is recommended to clean it with a water

humid sponge or clothe and a little bit of neutral soap.

diluted in large quantity of water.

If this doesn't work, use a soft brush instead of a cloth,

to rub the stain.

Be careful and do not use hard chemicals products that

can affect the fibers.

30 Kg. - 0,92m3 325 cm / 127,95"

COM FABRIC (137 cm width) **OTHERS**

BOX WEIGHT - VOLUME

Suitable for outdoor use. Resistant to weathering and sunlight

COUNTRY OF ORIGIN

Designed and Manufactured in Barcelona, Spain.

Iroko may change color or even crack due to humidity levels and sudden changes in temperature. Iroko undergoes a natural process of oxidation that affects its color, which turns a silver-grey shade. Iroko furniture is treated with a wate sealant. We recommend treating the wood twice a year:

1. Dampen a rag with soap solution and gently wipe the surface the wood. The soap solution will free the surface of dust and contaminating agents from pollution.

contaminating agents from pollution.

2. Once the soap solution has dried we will proceed to the app of the Cromaprotect water based re-toner. Dampen a sponge v re-toner and apply onto the surface of the wood you want to t