





BASE





**TECHNICAL DATA** 

**TEJA 2 SEATER SOFA** Design: Studio La Mamba

191x95x91 75,1"x37,4"x35,8"

Av. J.V. Foix 72-74 08034 Barcelona Spain

Tel.: +34 93 205 75 95 info@bivaq.com www.bivaq.com

FRAME Material Extruded aluminum **Finish** Polyester powder coating

Extruded aluminum / Polyester powder coating

1. Material / Finish

2. Material / Finish Iroko wood / Waterproof sealant

ROPE Cover material Polyester

Core material Polypropylene **UVA** resistance 7 (clasif. max. 8) **Color fastness** 5 (clasif. máx. 5)

**CUSHIONS** Material Polyurethane foam

100% polieter fiber Composition

Density 25 Kg/m3

**CUSHIONS FABRIC** Material Vinytex fabric: synthetic fabric made of plastic coated polyester

or Acrylic fabric: 100% solution dyed acrylic.

**UVA** resistance 7-8 (clasif. max. 8) **Color fastness** 5 (clasif. máx. 5)

**COLORS** See available colors at Bivag current Catalog.

MANTEINANCE Painted aluminum Clean the surface regularly with warm water and neutr Iroko wood

Use a non-abrasive sponge or cloth.

Rinse with plenty of water immediately after cleaning.

Rope & cushions It is recommended to clean it with a water

humid sponge or clothe and a little bit of neutral soap.

diluted in large quantity of water.

If this doesn't work, use a soft brush instead of a cloth,

to rub the stain.

Be careful and do not use hard chemicals products that

can affect the fibers.

**BOX WEIGHT - VOLUME** 43 Kg. - 1,62m3 COM FABRIC (137 cm width) 650 cm / 255,90"

**OTHERS** Suitable for outdoor use. Resistant to weathering and sunlight

COUNTRY OF ORIGIN Designed and Manufactured in Barcelona, Spain. Iroko may change color or even crack due to humidity levels and sudden changes in temperature. Iroko undergoes a natural process of oxidation that affects its color, which turns a silver-grey shade. Iroko furniture is treated with a wate sealant. We recommend treating the wood twice a year:

- 1. Dampen a rag with soap solution and gently wipe the surface the wood. The soap solution will free the surface of dust and contaminating agents from pollution. contaminating agents from pollution.
- 2. Once the soap solution has dried we will proceed to the app of the Cromaprotect water based re-toner. Dampen a sponge v re-toner and apply onto the surface of the wood you want to t